

FORM FOR CERTIFICATE – CLASS A SAFETY VALVE Part NO 34SV

This safety valve marked;

- **Maker's Name:** R. Conrader
- **Model Name:** SRV530
- **Serial Number:** SRV530

is of a design which has been the subject of tests with compressed air in accordance with ASME Boiler & Pressure Vessel Code, Section VIII, Division 1 and complying with Australian Standard AS 1271 for Class A safety valves, resulting in a rated slope of 3.35 SCFM/psia (.229 L/S per kPa) for that fluid. When fitted with spring no: 4468 with a spring rate of 54.52 lbf/in (9.55 N/mm) and a free length of 2.050 in (52.07 mm), it has lift of at least 0.20 in (5.08 mm) and a minimum discharge area of .782 in² (504.68 mm²) and consequently a rated discharge capacity at a set pressure of 160 psig (1100 kPa) and an over pressure of 10% or 3 psi (20 kPa), whichever is greater, of 638 SCFM (301.10 L/S) of compressed air at 20°C. National Board Capacity Certificate No: RCC-M13532 certifies the rated slope. Values converted to SI units are not confirmed by empirical results.

The set pressure of this valve may be adjusted within the limits of 0 psi (0 kPa) and any such adjustment will invalidate the rated slope stated above.

Nicholas R. Petrus
Engineering Manager



July 2, 2019

NSW:

115 Beaconsfield St
Silverwater NSW 2128
PH : (02) 9648 3099
FAX : (02) 9648 3362

QLD:

2/339 Archerfield Road
Richlands QLD 4077
PH : 07 3279 1213

VIC:

PH : 1300 667 579
FAX : (02) 9648 3362

**SA:(Statewide
Agencies P/L)**

PH : 1300 667 579
FAX: (08) 8264 5852

**WA: (Air & Power
P/L)**

7-9 Fisher St
Belmont WA 6904
PH : (08) 9479 4220
FAX : (08) 9277 4040